



Size	GD	A	B	C	D	E	F	G	H	J	K	M	N	O	P	R	U	V	keyway	W	AC	A'	E'	O'	P'	R'	oil capacity		approx. weight
																											side outlet	top outlet	
1702J	1 3/4	5 1/4	5 5/16	9 1/8	3	2 1/4	2 9/32	3 1/16	5 1/16	2 1/8	1 7/16	2 5/8	1 7/8	7 3/8	7 1/2	1 3/8	5625	1 3/8	1/8 X 1/16	1 1/2	3 7/8	3 1/2	3 1/8	6 3/4	7	1 3/8	3 1/8 FL OZ.	2 7/8 FL OZ.	25 LB
1704J	"	"	7 3/32	11	"	"	3 3/16	"	"	"	"	3 9/16	"	"	"	"	"	"	"	2	"	"	"	"	"	"	"	"	"
1707J	"	"	9 1/2	13 5/16	"	"	4 3/8	"	"	"	"	4 3/4	"	"	"	"	"	"	"	2 1/2	"	"	"	"	"	"	"	"	
2504J	2 1/2	6 1/2	7 1/2	11 3/8	4	2 7/8	3	1/4	5 1/16	2 1/4	2	3 7/16	1 5/16	9 7/8	9 1/2	1 1/2	7500	1 3/8	3/16 X 3/32	2 1/2	5 1/4	4 1/2	4 1/8	8 3/4	9 1/8	1 5/8	6 5/8 FL OZ.	8 1/2 FL OZ.	50 LB
2506J	"	"	10 5/32	14	"	"	4 5/16	"	"	"	"	4 29/32	"	"	"	"	"	"	"	3	"	"	"	"	"	"	"	"	
2510J	"	"	13 1/2	17 3/8	"	"	6	"	"	"	"	6 7/16	"	"	"	"	"	"	"	4	"	"	"	"	"	"	"	"	

APPROVED FOR CONSTRUCTION

Customer _____

Customer order no. _____ Roots no. _____

Date _____ By _____

V-BELT DRIVE SPECIFICATIONS

Belts _____

P.D. Drive sheave _____

P.D. Drive sheave _____

Center distance _____

Roots Blower and Vacuum Pump Division

DRESSER INDUSTRIES, INC.

CONNERSVILLE, INDIANA

8401-022

Printed in U.S.A. REV. PER ECN-2257 WMS 9-14-71 1700 UNITS "G" & "K" DECR. 1/16 3/16 2-13-70 ECN 2127V Dr. 3.2 Chk'd J.S.